

Dyson - Bug #200

MariaDB start script uses uninitialized array MYSQLD

2019-11-15 01:59 PM - Igor Pashev

Status:	New	Start date:	2019-11-15
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
Description			
<pre>#!/bin/bash set -euo pipefail DEFAULTS_FILE=/etc/mysql/my.cnf mysql_get_param() { "\${MYSQLD[@]}" --print-defaults \ tr " " "\n" \ grep -- "--\$1" \ tail -n 1 \ cut -d= -f2 echo "\$2" } DATADIR=\$(mysql_get_param 'datadir' '/var/lib/mysql') SOCKET=\$(mysql_get_param 'socket' '/var/run/mysql/mysql.sock') PID_FILE=\$(mysql_get_param 'pid-file' '/var/run/mysql/mysql.pid') USER=\$(mysql_get_param 'user' 'mysql') GROUP=\$(id -n -g "\$USER") MYSQL=(/usr/bin/mysql --defaults-file="\$DEFAULTS_FILE") MYSQLD=(/usr/sbin/mysql --defaults-file="\$DEFAULTS_FILE") MYSQLD+=(--datadir="\$DATADIR") MYSQLD+=(--pid-file="\$PID_FILE") MYSQLD+=(--socket="\$SOCKET") MYSQLD+=(--user="\$USER") ...</pre>			